

Package: AOV1R (via r-universe)

August 24, 2024

Type Package

Title Inference in the Balanced One-Way ANOVA Model with Random Factor

Version 0.1.0

Author Stéphane Laurent

Maintainer Stéphane Laurent <laurent_step@outlook.fr>

Description Provides functions to perform statistical inference in the balanced one-way ANOVA model with a random factor: confidence intervals, prediction interval, and Weerahandi generalized pivotal quantities. References: Burdick & Graybill (1992, ISBN-13: 978-0824786441); Weerahandi (1995) <doi:10.1007/978-1-4612-0825-9>; Lin & Liao (2008) <doi:10.1016/j.jspi.2008.01.001>.

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

Imports cellranger, purrr, stats, data.table, lazyeval, utils

RoxygenNote 7.1.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Date/Publication 2020-11-10 10:00:08 UTC

Repository <https://laustep.r-universe.dev>

RemoteUrl <https://github.com/cran/AOV1R>

RemoteRef HEAD

RemoteSha 230941f1c4d8b55a83e4aadf2946d97b65f86d93

Contents

aov1r	2
confint.aov1r	3
KM41	4
predict.aov1r	4
rGPQ	5
simAOV1R	6

Index	7
--------------	----------

aov1r	<i>One-way random effect ANOVA</i>
-------	------------------------------------

Description

Fits a one-way random effect ANOVA model.

Usage

```
aov1r(formula, data = NULL)

## S3 method for class 'aov1r'
summary(object, ...)

## S3 method for class 'summary.aov1r'
print(x, ...)
```

Arguments

formula	a formula of the form $y \sim \text{group}$
data	optional dataframe
object	an aov1r object (output of an aov1r call)
...	ignored
x	output of summary

Value

aov1r returns an object of class aov1r;

Examples

```
dat <- simAOV1R(I=2, J=3, mu=10, sigmab=1, sigmaw=1)
fit <- aov1r(y ~ group, data=dat)
summary(fit)
```

confint.aov1r	<i>Confidence intervals</i>
---------------	-----------------------------

Description

Confidence intervals for the one-way random effect ANOVA.

Usage

```
## S3 method for class 'aov1r'  
confint(object, parm, level = 0.95, SDs = TRUE, ...)  
  
## S3 method for class 'confint.aov1r'  
print(x, ...)
```

Arguments

object	an output of <code>aov1r</code>
parm	ignored
level	confidence level
SDs	logical, whether to return confidence intervals about the standard deviations or about the variances
...	ignored
x	an output of <code>confint</code> applied to an <code>aov1r</code> object

Value

A dataframe providing the bounds of the confidence intervals.

References

Richard K. Burdick, Franklin. A. Graybill. *Confidence Intervals on Variance Components*. CRC Press; 1st edition (1992). ISBN-13: 978-0824786441.

Examples

```
dat <- simAOV1R(I=2, J=3, mu=10, sigmab=1, sigmaw=1)  
fit <- aov1r(y ~ group, data=dat)  
confint(fit)
```

`KM41`*Krishnamoorthy & Mathew's example 4.1*

Description

The dataset used in Krishnamoorthy & Mathew's example 4.1.

Usage

```
data(KM41)
```

Format

A data frame with 25 rows and 2 columns.

References

Krishnamoorthy and Mathew, Statistical Tolerance Regions, Wiley 2009.

Examples

```
data(KM41)
str(KM41)
table(KM41$Batch)
```

`predict.aov1r`*Prediction interval for one-way random effect ANOVA*

Description

Prediction interval for the one-way random effect ANOVA model, based on a Satterthwaite approximation of the degrees of freedom.

Usage

```
## S3 method for class 'aov1r'
predict(object, level = 0.95, ...)
```

Arguments

<code>object</code>	an output of <code>aov1r</code>
<code>level</code>	confidence level
<code>...</code>	ignored

Value

A vector of length two, the bounds of the prediction interval.

References

T. Y. Lin, C. T. Liao. *Prediction intervals for general balanced linear random models*. Journal of Statistical Planning and Inference 138 (2008), 3164 – 3175. <doi:10.1016/j.jspi.2008.01.001>

Examples

```
dat <- simAOV1R(I=2, J=3, mu=10, sigmab=1, sigmaw=1)
fit <- aov1r(y ~ group, data=dat)
predict(fit)
```

rGPQ

Generalized pivotal quantities

Description

Simulates from the generalized pivotal quantities.

Usage

```
rGPQ(fit, n = 10000)
```

Arguments

fit	an <code>aov1r</code> object
n	number of simulations

Value

The simulations in a dataframe.

References

Samaradasa Weerahandi. *Exact Statistical Methods for Data Analysis*. Springer, New York, NY (1995). <doi:10.1007/978-1-4612-0825-9>

Examples

```
dat <- simAOV1R(I=20, J=5, mu=10, sigmab=1, sigmaw=1)
fit <- aov1r(y ~ group, data=dat)
nsims <- 20000
pivsims <- rGPQ(fit, nsims)
pivsims$GPQ_sigma2tot <- pivsims$GPQ_sigma2b + pivsims$GPQ_sigma2w
# Generalized confidence intervals:
lapply(pivsims, quantile, probs = c(0.025, 0.975))
```

```
# compare with the frequentist confidence intervals:
confint(fit, SDs = FALSE)
# Generalized prediction interval:
with(
  pivsims,
  quantile(rnorm(nsim, GPQ_mu, sqrt(GPQ_sigma2tot)),
    probs = c(0.025, 0.975))
)
# compare with the frequentist prediction interval:
predict(fit)
```

simAOV1R

Simulation of one-way random effect ANOVA

Description

Simulates a balanced one-way random effect ANOVA model.

Usage

```
simAOV1R(I, J, mu, sigmab, sigmaw)
```

Arguments

I	integer, number of groups
J	integer, number of replicates per group
mu	numeric, overall mean
sigmab	positive number, the between standard deviation
sigmaw	positive number, the within standard deviation

Value

A dataframe.

Examples

```
simAOV1R(I=2, J=3, mu=10, sigmab=1, sigmaw=1)
```

Index

* data

KM41, 4

aov1r, 2, 3–5

confint.aov1r, 3

KM41, 4

predict.aov1r, 4

print.confint.aov1r (confint.aov1r), 3

print.summary.aov1r (aov1r), 2

rGPQ, 5

simAOV1R, 6

summary.aov1r (aov1r), 2